



GVM/24 PCM



Lubricated coaxial compressor with high-efficiency 'V' pumping unit.

Two-cylinder, lubricated “V” compressor with high efficiency and high reliability pumping unit. Suitable for use with a wide range of pneumatic tools. The 3 hp pumping unit is fully protected by the steel structure with integrated 24 litre tank. The controls are centralised in the control panel for easy operation. The fixed handle integrated into the structure is suitable for transport either raised or pulled on wheels. The extendable handle allow for easy handling.

Technical data

|                                 |        |               |
|---------------------------------|--------|---------------|
| Product code                    |        | 3BXA504NUA    |
| Lubrication                     |        | Lubricated    |
| Compressor pump                 |        | GVM           |
| Air receiver (l)                |        | 24            |
| Power                           | HP     | 3             |
|                                 | kW     | 2,2           |
| Max. pressure                   | bar    | 10            |
|                                 | p.s.i. | 145           |
| Nr. of cylinders                |        | 2V            |
| Air displacement                | l/min. | 350           |
|                                 | c.f.m. | 12,4          |
| R.P.M.                          |        | 1450          |
| Voltage / Frequency (Volt / Hz) |        | 230 / 50      |
| Type motor                      |        | Electric      |
| Gross weight                    | kg     | 56            |
|                                 | lb     | 123           |
| Packaging dimensions LxWxH (mm) |        | 640x530x780   |
| EAN code                        |        | 8016738701500 |