

POLAR-E - POLAR-E PM

5.5-75 kW

Rotary screw compressors
with direct-drive transmission,
fixed speed and variable speed
with Permanent Magnet motor



NEW
2026 RANGE


FNA COMPRESSORS

80 years of compressed air.

FNA COMPRESSORS is a Multinational company with 80 years of experience in the compressed air sector, founded from the merger of three long-established Italian compressor companies, which has developed an industrial synergy capable of competing on the world market without fear of comparison. Thanks to the consolidated experience and leadership of a family that has been operating exclusively in the compressed air sector for two generations, FNA COMPRESSORS is one of the leading manufacturers of air compressors for industrial, professional and consumer use.

NUAIR, an integral part of the FNA COMPRESSORS family, is the industrial trademark, an undisputed leader in the design, development, production and distribution of high-tech solutions for compressing air with the greatest possible energy savings, serving every sector, from large industry to small business.

NUAIR's screw compressors, in the 2.2 to 75 kW power range, are manufactured entirely in Italy in the province of Bologna, an area renowned for its excellence in precision engineering, where the most modern design, construction, assembly and testing technologies are applied to ensure customers reliable compressors with first-class performance.



Facts and figures

1.500.000	Piston compressors produced per year
11.000	Screw compressors produced per year
1.500	Global service centres
1.300	Employees
300	Million € turnover
120	Countries we export to
7	Manufacturing plants

The NUAIR brand

Manufacturers of air-ends for over 30 years.

NUAIR is the leading Italian company, that has been able to combine craftsmanship passion with the most modern industrial technologies, integrating highly specialised labour with last-generation automatic machinery. The Made in Italy trademark is the expression of typical Italian quality and creativity, recognised and appreciated around the world, and which is now one of the distinguishing elements of our industrial production.

What makes NUAIR screw compressors unique is the guarantee of a product that is made entirely in Italy: from design to packaging, each stage of production is carefully overseen by our engineers and aimed at developing a machine that exceeds the most demanding requirements in terms of reliability, energy saving, performance, quiet and safe operation.

NUAIR air-ends, the true heart of our compressors, feature rotors with an optimised profile and outstanding performance. Their production process is completely integrated thanks to robotic machine tools and sophisticated control instrumentation that guarantees the highest level of quality. Each single rotor is machined in four very specific stages to achieve high precision and repeatability.

Before reaching the customer, every individual compressor is fully tested before completing final checks that ensure total compliance with over fifty stringent technical requirements.

Since 1996, the company's Quality System has been certified according to UNI EN ISO 9001:2015.



POLAR-E 5.5-15 kW

POLAR-E PM 5.5-75 kW

Compact, silent, efficient and ready to use.
Available in multiple versions to suit many applications.

NUAIR's new POLAR-E series screw compressors provide a high-performance solution for the most demanding applications. Designed to fulfill compressed air requirements in terms of reliability, energy efficiency, quiet operation, reduced maintenance costs, and simple installation and use, the POLAR-E range offers a broad selection of models, from 5.5 to 75 kW with operating pressures between 8 and 13 bar, available with or without air receiver or dryer. Each compressor is built according to the highest standards, using high quality components, to guarantee a long operating life and complete reliability. The motor shaft is coaxial to the rotor of the air-end: this configuration means less wear on components, therefore less need for maintenance and quieter operation in comparison to belt transmission.



With the introduction of the latest PM models to the renowned POLAR-E series, NUAIR is once more redefining the standards in respect to efficiency, reliability and energy savings.

The continuous investment in Research & Development has allowed the further improvement to the acclaimed POLAR series, already a leading-edge product in the industrial market, by introducing Permanent Magnet Motors (with IE5 "Ultra Premium Efficiency" class). This is integrated with our direct transmission system and optimised controls in the form of the highly advanced LOGIN electronic controller. These innovative technologies, combined with the application of our latest generation air-ends, has allowed to build the most advanced, quiet, reliable and efficient compressor ever.



A complete and versatile range, 7 sizes, from 5.5 to 75 kW with more than 90 possible configurations!

POLAR-E 5.5-15 kW - FIXED SPEED

Size	Power (kW)	Model	Fixed speed	Floor mounted	With air receiver	With air receiver + dryer (D)	Air-end	Electronic controller	Motor efficiency
1	5.5	POLAR-E 5.5	•	•	270 ℓ	270 ℓ	FS26	LOGIN Mini	IE3
	7.5	POLAR-E 7.5	•	•	270-500 ℓ	270-500 ℓ	FS26	LOGIN Mini	IE3
2	11	POLAR-E 11	•	•	500 ℓ	500 ℓ	FS50	LOGIN Mini	IE3
	15	POLAR-E 15	•	•	500 ℓ	500 ℓ	FS50	LOGIN Mini	IE3

POLAR-E PM 5.5-15 kW - VARIABLE SPEED WITH PERMANENT MAGNET MOTOR

Size	Power (kW)	Model	Variable speed with Permanent Magnet Motor	Floor mounted	With air receiver	With air receiver + dryer (D)	Air-end	Electronic controller	Thermostatic valve	Motor efficiency
3	5.5	POLAR-E 5.5 PM	•	•	270-500 ℓ	270-500 ℓ	FS26	LOGIN	•	IE5
	7.5	POLAR-E 7.5 PM	•	•	270-500 ℓ	270-500 ℓ	FS26	LOGIN	•	IE5
	11	POLAR-E 11 PM	•	•	500 ℓ	500 ℓ	FS50	LOGIN	•	IE5
	15	POLAR-E 15 PM	•	•	500 ℓ	500 ℓ	FS50	LOGIN	•	IE5

POLAR-E PM 18.5-75 kW - VARIABLE SPEED WITH PERMANENT MAGNET MOTOR

Size	Power (kW)	Model	Variable speed with Permanent Magnet Motor	Floor mounted	Air-end	Electronic controller	Thermostatic valve	Motor efficiency
4	18.5	POLAR-E 18.5 PM	•	•	FS100	LOGIN	•	IE5
	22	POLAR-E 22 PM	•	•	FS100	LOGIN	•	IE5
5	30	POLAR-E 30 PM	•	•	FS140	LOGIN	•	IE5
	37	POLAR-E 37-10 PM	•	•	FS140	LOGIN	•	IE5
6	37	POLAR-E 37-08 PM	•	•	FS270	LOGIN	•	IE5
	45	POLAR-E 45 PM	•	•	FS270	LOGIN	•	IE5
7	55	POLAR-E 55 PM	•	•	FS320	LOGIN	•	IE5
	75	POLAR-E 75 PM	•	•	FS400	LOGIN	•	IE5

POLAR-E 5.5-15 kW FIXED SPEED



Efficiency and energy savings

Significant energy savings thanks to “IE3 Premium Efficiency” class motors. Direct 1:1 transmission based on an original NUAIR design.
Our own in-house air-ends offering the highest performance with the lowest energy consumption.
Air and oil circuit components are optimised for efficiency.
LOGIN Mini electronic controller for complete control of all compressor functions.



LOGIN Mini controller

All POLAR-E 5.5-15 models are equipped with the LOGIN Mini electronic controller with colour display. In addition to full control of all compressor functions, it also manages multiple compressors (up to 8 units, even different types) and features an RS485 port with an integrated Modbus protocol for communication with external devices.



Quiet operation

The low speed air-ends and radial fans allow POLAR-E compressors to maintain the lowest noise values in their category, thus ensuring the possibility for the installation close to the point-of-use.



Simplified maintenance

All machine parts subject to periodic maintenance are placed in a visible and easily accessible position.
Maintenance costs are reduced thanks to the use of selected, top quality materials.




Robust construction

The compact design has been created to achieve the best performance with the utmost reliability, tested and proven in thousands of installations around the world. This makes POLAR-E machines dependable and long-lasting.



Refrigerated dryer and filters (optional)

The POLAR-E version from 5.5 to 15 kW with air receiver can be equipped with F-DRY, a +3 °C dew point refrigerated dryer, and retrofitted with line filters, mounted on the rear of the air receiver.



F-DRY dryer

Models equipped with the F-DRY, a +3 °C DEW POINT refrigerated dryer, are complete, ready-to-use machines, with no additional installation costs.



A complete solution

For all POLAR-E from 5.5 to 15 kW with air receiver and dryer, a retrofttable **optional filter set** is available (including oil and fine oil filters with total filtration degree 0.01 micron and oil residual 0.01 mg/m³) to obtain a complete workstation.

Model	Motor power	Air receiver	Dryer	Connection	Air flow rate	Filter kits
	kW	lt	model	G	m³/min.	code
POLAR-E 5.5 - 7.5	5.5 - 7.5	270 - 500	F-DRY 18	1"	1.8	C260KFL060
POLAR-E 11 - 15	11 - 15	500	F-DRY 25	1"	2.5	

POLAR-E PM 5.5-75 kW

VARIABLE SPEED WITH PERMANENT MAGNET MOTOR



Maximum efficiency and energy saving

Significant energy savings are achieved thanks to the "IE5 Ultra Premium Efficiency" class in the POLAR-E PM models. The latest generation air-ends ensure greater compressed air flow rates with reduced energy consumption. Direct-drive transmission technology. The oil circuit is controlled by the thermostatic valve, guaranteeing ideal and constant temperature. Application of the latest generation inverters combined to the high energy efficiency Permanent Magnet motors.



LOGIN controller

All POLAR-E PM models are equipped with the LOGIN electronic controller with touch-screen display. In addition to full control of all compressor functions, it also stores the data on a specific memory card, for compressor data restore. Ref. to page 18 for controller extensive description.



Simplified maintenance

All machine parts subject to periodic maintenance are placed in a visible and easily accessible position. Maintenance costs are reduced thanks to the use of selected, top quality materials.



Compact design

The POLAR-E PM series has been designed to offer maximum performance and highest reliability, in a compact space saving format.



Remote monitoring and preventive maintenance

LOGIN controller features RS485 ports for communication with remote systems via Modbus protocol. Furthermore, the "ISC" system (Internal Sequencing of Compressors) allows up to 8 different compressors (fixed and/or variable speed) to be sequenced using master-slave functionality.




Refrigerated dryer and filters (optional)

The POLAR-E PM version from 5.5 to 15 kW with air receiver can be equipped with F-DRY, a +3 °C dew point refrigerated dryer, and retrofitted with line filters, mounted on the rear of the air receiver.



F-DRY dryer

Models equipped with the F-DRY, a +3 °C DEW POINT refrigerated dryer, are complete, ready-to-use machines, with no additional installation costs!



Very high efficiency motors

IE5 "Ultra Premium Efficiency" Permanent Magnet motors, with IP55 protection as standard on all POLAR-E PM models.



Cleaning and protection

The ventilation circuit is protected by a pre-filtering panel (standard on all POLAR-E PM models) that separates the incoming dusts and keeps the inside of the machine clean, increasing the longevity of internal components.



POLAR-E PM 5.5-15 kW

VARIABLE SPEED WITH PERMANENT MAGNET MOTOR


A complete solution with air receiver + optional dryer and filters

The POLAR-E PM with optional dryer and filters is a full feature compressed air station: all the fundamental components that form a complex system are assembled conveniently into workstation, saving space and improving efficiency.

- Air compressor.
- Air receiver (270 or 500 lt).
- Integrated refrigerated dryer with +3 °C dew point and with automatic condensate drain.
- Installed oil and fine oil filters with total filtration degree 0.01 micron and oil residual 0.01 mg/m³.
- LOGIN electronic controller.
- Application of the latest generation inverters combined to the high energy efficiency Permanent Magnet motors.

Significant advantages:

- Drastically reduced installation time and cost.
- High quality, clean and dry compressed air.
- The maintenance friendly design allows complete and simple access to all service components, reducing costs and downtime.
- Lower operating costs.
- The thermostatic valve regulates the oil temperature, preventing the formation of condensation inside the oil-separator vessel.
- Clear visualization of all operating values of the compressor on the large clear display from the proven LOGIN controller.



POLAR-E PM with optional dryer and filters is a very user friendly compressor, perfect for industrial and automotive situations or any application that requires dry and clean compressed air, with minimal space requirement.

ALL-IN-ONE SOLUTION:

- 1 compressor
- 2 air receiver
- 3 dryer
- 4 filters



Model	Motor power	Air receiver	Dryer	Connection	Air flow rate	Filter kits
	kW	lt	model	G	m³/min.	code
POLAR-E 5.5 - 7.5 PM	5.5 - 7.5	270	F-DRY 18	1"	1.8	C260KFL060
POLAR-E 11 - 15 PM	11 - 15	500	F-DRY 25	1"	2.5	

For all POLAR-E PM from 5.5 to 15 kW with air receiver and dryer, a retrofittable **optional filter set** is available (including oil and fine oil filters with total filtration degree 0.01 micron and oil residual 0.01 mg/m³) to obtain a complete workstation.

POLAR-E PM 18.5-75 kW

VARIABLE SPEED WITH PERMANENT MAGNET MOTOR

Air filter
Easily accessible for easy maintenance. Single or two stage air filter, depending on the model. The carefully designed service items allow long operating life, guarantee excellent reliability and reduced maintenance costs.

Minimum pressure valve
Guarantees minimum pressure loss.

Thermostatic valve
Controls the oil flow granting constant working temperatures and preventing the formation of condensate inside the lubrication circuit.

Intake regulator
The intake regulator controls operation of the compressor to ensure minimum pressure during idle operation, resulting in lower power consumption.

Direct transmission, with latest generation air-ends
The motor shaft is coaxial to the rotor of the air-end: this configuration means less wear on components, therefore less need for maintenance and quieter operation in comparison to belt transmission. This innovative design, combined with IE5 motors, guarantees superior efficiency and reliability.



Monoblock drive housing for air-end-motor connection
Allows quick access for inspection and replacement of the coupling.



Heat exchanger
Carefully designed to combine highly efficient heat transfer in all conditions and reduced pressure losses.

Simplified maintenance
Fast and simple routine maintenance thanks to the large removable panels offering unhindered access to the internal components.

Fan and radiator inspection ports
In the POLAR-E PM 18.5 to 75 kW models, the compartment hosting the fan is accessible via two inspection doors which also allow counterflow cleaning of the radiator.

Cooling system
The radiator and radial fan are mounted in a dedicated compartment that maximizes the thrust of the outgoing air and allows the compressor to be used even with the open doors.


Radial ventilation
This combines excellent cooling of the compressor with very quiet operation.



Pre-filtration panels
The ventilation circuit is completed by pre-filter panels that separate incoming dust, protecting internal components for a longer service life.



External greasing points
The greasing points for the main electric motor bearings are accessible from the outside of the compressor, allowing safe lubrication, even with the machine running.



Very high efficiency motors
IE5 "Ultra Premium Efficiency" Permanent Magnet synchronous motors with IP55 protection on all variable speed POLAR-E PM between 5.5 and 75 kW.



POLAR-E PM with variable speed and Permanent Magnet synchronous IE5 motor


Why choose an air compressor with Permanent Magnet motor?

The energy costs linked to an air compressors operation during its life cycle represent more than 80% of the total life cycle costs.

For NUAIR the improved energy efficiency of its products is a key objective. This objective is achieved with the use of Permanent Magnet motors in IE5 "Super Premium Efficiency" category, along with the employment of our own, latest generation compressor air-ends.

The application of these cutting - edge technologies, provides all users an air compressor with superior energy saving characteristics.

The compressors from this new range offer greater flexibility in the delivery of compressed air. The output flow of compressed air may span a capacity range of between 15% to 100% of the maximum flow rate. This makes possible to greatly reduce unloaded operation, saving significant amounts of energy and minimising component wear, whilst adding greater reliability and longer service life.




The graph represents the total life cycle costs breakdown of a 37 kW fixed speed compressor, over 5 years of use, considering 4000 working hours per year and an energy cost of about 0.17 €/kWh.

Why choose a POLAR-E PM?

- Permanent Magnet motor with IE5 efficiency.
- Latest generation air-ends.
- Direct transmission.
- Efficient intake regulator.
- High performing inverter.
- Intuitive touchscreen controller.
- Low noise levels.
- High quality components.
- Minimum maintenance.



For the variable speed models with PM motors, we use direct transmission with flexible coupling starting from 18,5 kW.




The advantages offered by the POLAR-E PM range are considerable:

- The compressed air generated is aligned to the system requirements and is achieved by regulating the speed of the electric motor, which can range from 15% to 100% of the maximum speed.
- Excellent and precise pressure control thanks to the permanent magnet synchronous motor.
- Accurate and optimised cooling of the compressor is obtained through the use of efficient, powerful and quiet radial fans.
- Proven, highly reliable design.
- Attention to details, to maximise quiet operation and reliability.

Improved efficiency in all applications of compressed air.

The advanced and extremely compact Permanent Magnet motors, guarantee the highest performance along with a much wider speed/load range when compared to traditional inverter-controlled asynchronous motors. They offer the greatest possible advantages in terms of energy savings. This applies especially when used at partial capacity and load, which is a characteristic seen frequently in modern applications throughout all industrial sectors.




More efficient than ever

The inverter, installed in the compressor's electrical panel allows for a dynamic regulation of the motors rotational speed. The speed and therefore the output of the compressor can be constantly adjusted according to demand. This also eliminates current surges thanks to the soft start-up and drastically reduces operating cycles avoiding unnecessary no-load operation, avoiding significant energy wastage and reducing energy costs.

Significant energy savings

When compared to the operation of a fixed speed compressor, a POLAR-E PM is able to achieve significant energy savings, up to 50%. This represents a reduction of around 30% to the total life cycle costs during 5 years of use.



Efficiency is synonymous with sustainability

For all companies, environmental sustainability is a most important objective and a focus on the efficiency of all processes is mandatory. Working and living sustainably means preserving our natural resources as much as possible: choosing a POLAR-E or POLAR-E PM product, reducing energy consumption and CO₂ emissions therefore, represents an ecological and sensible choice.



The calculation shown in the graphs is based on the energy analysis of a 37 kW POLAR-E PM, considering 4000 working hours per year and an energy cost of about 0.17 €/kWh.



Analyze your company's consumption to minimize energy waste

Compressed air is an essential resource in industrial applications, as well as one of the main sources of energy consumption. Energy costs are constantly increasing, therefore it is a fundamental need to monitor, analyse and reduce the energy consumption of the compressed air system. This not only applies for large companies, but equally for medium and small-sized facilities.

Why run an energy audit?

Compressed air is most critical to production and manufacturing operations everywhere. The energy audit provides a valuable analysis of the system, identifying all operating data including power consumption. The very precise data collected is then used to provide a simulation report, identifying opportunities for reducing energy consumption and improving efficiencies.

Our experience at your service

Thanks to decades of experience in the industrial sector, NUAIR can provide companies with a detection and analysis service for professional auditing (EATool). Furthermore, with "Demo Login" it is possible to simulate compressor operation to provide immediate technical assistance remotely and/or use it as a tool to train maintenance technicians and installers on the full operation of the LOGIN controller.



	ideal for compressors' rooms up to 3 units
EA 400 cod. 9062747	➤ 4 analogue inputs: - 3 measuring clamps - 1 pressure sensor ➤ 1 extension for cables (10m long) ➤ 4.3" colour touch screen display
	ideal for compressors' rooms up to 4 units
EA 500 cod. 9062748	➤ 5 analogue inputs: - 4 measuring clamps - 1 pressure sensor ➤ 2 extensions for cables (10m long) ➤ 7" colour touch screen display

	ideal for technical assistance and training
DEMO LOGIN cod. 8101980	➤ complete simulation of the functions of a compressor controlled from Login ➤ 3 potentiometers (pressure, oil temperature values, dryer temperature) ➤ 7 switches (alarm simulation and remote control)





Efficiency that is always under control

Installed on POLAR-E PM models from 5.5 to 75 kW, the new **LOGIN** controller introduces new software functions to enhance diagnostic controls, thereby guaranteeing excellent performance in all conditions, facilitating remote control and multi-compressor management.



Intelligent control

All of POLAR-E PM's functions are entirely managed by the LOGIN electronic controller, which constantly monitors the compressor status ensuring efficient and reliable operation of the machine in all conditions with customised functions to suit any application.

Always connected

During an irregular event within the machine, LOGIN reports the presence of such and incident by creating an alert for the user, allowing prompt operator intervention. The integrated connectivity with remote monitoring (optional), makes possible to get complete information on the compressor status remotely.


Compressor rotation management

Thanks to the 'ISC' system (Internal Sequencing of Compressors), up to 8 different compressors (fixed and/or variable speed) can be connected simultaneously, with 'master-slave' logic. The LOGIN controller features an RS485 port with an integrated Modbus protocol for communication with external devices.



Exclusive design

Italian design, functionality, simple to use and with the latest generation technology all come together with the innovative Login controller. The touch-screen display and the icon-based menu make it extremely intuitive and easy to use.



Memory card slot

LOGIN features a memory card slot which can be used to store compressor data and configurations and to transfer them to another control unit.



Multilingual management

It is possible to select the local language or any one of 20 pre-installed languages.



Remote control

Allows a complete remote monitoring of the compressor.



Multicolour display

All of the operational parameters are displayed on the large 4.3" colour screen which also displays graphs in real time (pressure, power, energy/time).






Designed for Industry 4.0



Intuitive and efficient.

Installed on the 5.5 to 15 kW POLAR-E series, the **LOGIN Mini** is a digital electronic controller featuring six buttons for complete control of all compressor functions. The multilingual colour display, intuitive and complete, displays extended text.



- Menu navigation is simplified by icons displayed on the bottom navigation bar.

- Pressure is continuously monitored via a dedicated sensor and compared with the setpoints of the controller, ensuring optimal compressor operation.

- The simple and effective motor control monitors both temperature and running/idling cycles, ensuring all operational parameters are met and maximising reliability.

- Thanks to the native ISC function (Internal Sequencing of Compressors), the controller can manage up to 8 units in master/slave mode.

- The LOGIN Mini features an RS485 port with an integrated Modbus protocol for communication with external devices.

- Configurable auto-restart and remote ON/OFF complete the LOGIN Mini's extensive feature set.



Intuitive interface

The display features two permanently visible bars: a status bar at the top and a navigation bar at the bottom. This allows the user to view the status of the machine and the active functions at any time.



Multilingual management

It is possible to select the local language or any one of 20 pre-installed languages.



Multi-compressor management

Allows simultaneous management of up to 8 machines, in master/slave mode.



Multicolour display

All operating parameters are shown on the 2.4" colour display.



Remote control

Allows compressor remote control.



Designed for Industry 4.0

POLAR-E
5.5-15 kW

<

ES = model with F-DRY refrigeration dryer with +3 °C dew point and automatic condensate drain (filters excluded - see page 7).
PM = model with variable speed and Permanent Magnet motor.
PM-ES = model with variable speed, Permanent Magnet motor and F-DRY refrigeration dryer with +3 °C dew point with automatic condensate drain.
Reference conditions: air intake temperature 20°C (68°F) – atmospheric pressure 1 bar (14.5 p.s.i.).
The data and results were measured in accordance with ISO 1217.
The sound level was measured in accordance with ISO 2151, with a tolerance of ±3 dB(A).

POLAR-E PM
5.5-15 kW

POLAR-E PM 5.5-15 kW	P/N	Tank	Power		Air outflow rate (min.-max)			Max. pressure		Air-end	Sound level	Ø	Net weight	Net dimensions	Gross weight	Gross dimensions
		ℓ	kW	HP	l/min	m³/min	cfm	bar	psi		dB(A)	G	kg	L x W x H (mm)	kg	L x W x H (mm)
VARIABLE SPEED with PERMANENT MAGNET MOTOR - LOGIN controller																
5.5 kW																
POLAR-E 5.5-08 PM	V60GS97N1NA55	-	5.5	7.5	140-940	0.14-0.94	5-33	8	116	FS26	60	3/4"	165	1020x690x960	185	1200x810x1220
POLAR-E 5.5-10 PM	V60GT97N1NA55	-	5.5	7.5	130-785	0.13-0.78	5-28	10	145	FS26	60	3/4"	165	1020x690x960	185	1200x810x1220
POLAR-E 5.5-08-270 PM	V91GS97N1NA55	270	5.5	7.5	140-940	0.14-0.94	5-33	8	116	FS26	60	3/4"	240	1510x690x1480	275	1720x750x1700
POLAR-E 5.5-10-270 PM	V91GT97N1NA55	270	5.5	7.5	130-785	0.13-0.78	5-28	10	145	FS26	60	3/4"	240	1510x690x1480	275	1720x750x1700
POLAR-E 5.5-08-270 PM-ES	V91GS97N1NB55	270	5.5	7.5	140-940	0.14-0.94	5-33	8	116	FS26	60	1"	290	1620x690x1480	325	1720x750x1700
POLAR-E 5.5-10-270 PM-ES	V91GT97N1NB55	270	5.5	7.5	130-785	0.13-0.78	5-28	10	145	FS26	60	1"	290	1620x690x1480	325	1720x750x1700
7.5 kW																
POLAR-E 7.5-08 PM	V60GV97N1NA55	-	7.5	10	310-1270	0.31-1.27	11-45	8	116	FS26	60	3/4"	165	1020x690x960	185	1200x810x1220
POLAR-E 7.5-10 PM	V60GW97N1NA55	-	7.5	10	310-1060	0.31-1.06	11-37	10	145	FS26	61	3/4"	165	1020x690x960	185	1200x810x1220
POLAR-E 7.5-13 PM	V60GX97N1NA55	-	7.5	10	300-621	0.30-0.62	11-22	13	189	FS26	61	3/4"	165	1020x690x960	185	1200x810x1220
POLAR-E 7.5-08-270 PM	V91GV97N1NA55	270	7.5	10	310-1270	0.31-1.27	11-45	8	116	FS26	61	3/4"	240	1510x690x1480	275	1720x750x1700
POLAR-E 7.5-10-270 PM	V91GW97N1NA55	270	7.5	10	310-1060	0.31-1.06	11-37	10	145	FS26	61	3/4"	240	1510x690x1480	275	1720x750x1700
POLAR-E 7.5-13-270 PM	V91GX97N1NA55	270	7.5	10	300-621	0.30-0.62	11-22	13	189	FS26	61	3/4"	240	1510x690x1480	275	1720x750x1700
POLAR-E 7.5-08-270 PM-ES	V91GV97N1NB55	270	7.5	10	310-1270	0.31-1.27	11-45	8	116	FS26	61	1"	290	1620x690x1480	325	1720x750x1700
POLAR-E 7.5-10-270 PM-ES	V91GW97N1NB55	270	7.5	10	310-1060	0.31-1.06	11-37	10	145	FS26	61	1"	290	1620x690x1480	325	1720x750x1700
POLAR-E 7.5-13-270 PM-ES	V91GX97N1NB55	270	7.5	10	300-621	0.30-0.62	11-22	13	189	FS26	61	1"	290	1620x690x1480	325	1720x750x1700
11 kW																
POLAR-E 11-08 PM	V60HA97N1NA55	-	11	15	620-1750	0.62-1.75	22-62	8	116	FS50	60	3/4"	210	1020x690x960	231	1200x810x1220
POLAR-E 11-10 PM	V60HB97N1NA55	-	11	15	580-1550	0.58-1.55	20-55	10	145	FS50	60	3/4"	210	1020x690x960	231	1200x810x1220
POLAR-E 11-13 PM	V60HC97N1NA55	-	11	15	375-1250	0.37-1.25	13-44	13	189	FS50	60	3/4"	210	1020x690x960	231	1200x810x1220
POLAR-E 11-08-500 PM	V83HA97N1NA55	500	11	15	620-1750	0.62-1.75	22-62	8	116	FS50	60	3/4"	325	1950x690x1580	365	2070x800x1850
POLAR-E 11-10-500 PM	V83HB97N1NA55	500	11	15	580-1550	0.58-1.55	20-55	10	145	FS50	60	3/4"	325	1950x690x1580	365	2070x800x1850
POLAR-E 11-13-500 PM	V83HC97N1NA55	500	11	15	375-1250	0.37-1.25	13-44	13	189	FS50	60	3/4"	355	1950x690x1580	395	2070x800x1850
POLAR-E 11-08-500 PM-ES	V83HA97N1NB55	500	11	15	620-1750	0.62-1.75	22-62	8	116	FS50	60	1"	370	1950x690x1580	410	2070x800x1850
POLAR-E 11-10-500 PM-ES	V83HB97N1NB55	500	11	15	580-1550	0.58-1.55	20-55	10	145	FS50	60	1"	370	1950x690x1580	410	2070x800x1850
POLAR-E 11-13-500 PM-ES	V83HC97N1NB55	500	11	15	375-1250	0.37-1.25	13-44	13	189	FS50	60	1"	400	1950x690x1580	440	2070x800x1850
15 kW																
POLAR-E 15-08 PM	V60HD97N1NA55	-	15	20	310-2600	0.31- 2.6	11-92	8	116	FS50	62	3/4"	215	1020x690x960	235	1200x810x1220
POLAR-E 15-10 PM	V60HE97N1NA55	-	15	20	340-2230	0.34-2.23	12-79	10	145	FS50	62	3/4"	215	1020x690x960	235	1200x810x1220
POLAR-E 15-13 PM	V60HF97N1NA55	-	15	20	585-1600	0.58-1.6	21-56	13	189	FS50	62	3/4"	215	1020x690x960	235	1200x810x1220
POLAR-E 15-08-500 PM	V83HD97N1NA55	500	15	20	310-2600	0.31- 2.6	11-92	8	116	FS50	62	3/4"	330	1950x690x1580	350	2070x800x1850
POLAR-E 15-10-500 PM	V83HE97N1NA55	500	15	20	340-2230	0.34-2.23	12-79	10	145	FS50	62	3/4"	330	1950x690x1580	350	2070x800x1850
POLAR-E 15-13-500 PM	V83HF97N1NA55	500	15	20	585-1600	0.58-1.6	21-56	13	189	FS50	62	3/4"	360	1950x690x1580	380	2070x800x1850
POLAR-E 15-08-500 PM-ES	V83HD97N1NB55	500	15	20	310-2600	0.31- 2.6	11-92	8	116	FS50	62	1"	375	1950x690x1580	395	2070x800x1850
POLAR-E 15-10-500 PM-ES	V83HE97N1NB55	500	15	20	340-2230	0.34-2.23	12-79	10	145	FS50	62	1"	375	1950x690x1580	395	2070x800x1850
POLAR-E 15-13-500 PM-ES	V83HF97N1NB55	500	15	20	585-1600	0.58-1.6	21-56	13	189	FS50	62	1"	405	1950x690x1580	425	2070x800x1850

Extend the life and efficiency of your screw compressor.

In addition to offering the highest quality and technologically advanced products, NUAIR focuses its attention on customer care and full technical and product support, identifying our customers' needs and the most suitable solutions. Our skilled and professional team grants assistance over the phone/email, technical on-site consultancy, personalised quotations, maintenance programmes, training programmes, etc.

The importance of original spare parts...

FSN is the brand of the original spare parts and after sales activities for all NUAIR compressors. FSN guarantees that the components are original and that they were carefully selected, checked and tested by skilled technicians. Using FSN certified original spare parts reduces management costs and guarantees the efficiency, reliability and longevity of the compressor. Our “Hot-Line” service guarantees the shipment of urgent spare parts within 24 hours from the order.

LONG LIFE KIT for the scheduled maintenance of screw compressors

To make maintenance planning simple and in accordance with the recommendations, NUAIR has developed its “LONG LIFE SERVICE KITS”, specifically created for all NUAIR screw compressor models. Using Long Life Kits ensures an extended service life, increased safety whilst ensuring maximum compressor performance.



Investment guaranteed up to 5 years! with the TRUST warranty extension

NUAIR believes so strongly in the quality and reliability of its compressors as to guarantee them up to 60 months! By choosing TRUST it is possible to extend the standard warranty period by 3 or 5 years, through a complete preventive maintenance program. There are many benefits: the customer can thereby avail of the qualified assistance of authorised technicians in complete safety, reducing the uncertainty of maintenance costs and foreseeing any downtime. Also, the use of original spare parts guaranteed by the FSN trademark will ensure that the compressor operates with maximum efficiency and for a longer service life. The “Trust” warranty can be easily extended online through EasyConnect portal on the website nuaircompressors.com.

... and specific lubricants

RotarECOFLUID 46 cSt mineral oil

C600000023	1 x 5-litre can (4.385 kg)
C600000021	1 x 20-litre can (17.36 kg)
C600000022	1 x 200-litre drum (174 kg)

Formulated with high quality selected mineral oil, this lubricant offers optimal control of oxidation and residue deposits as well as an excellent level of thermal stability and oxidation to ensure the longevity of equipment and continued high performance.

RotEnergyPlus 46 cSt synthetic oil

C600000024A	1 x 5-litre can (4.37 kg)
C600000007A	1 x 19-litre can (16 kg)
C600000012A	1 x 208-litre drum (181 kg)

Ensures quick water separation with reduced friction and energy consumption, provides long maintenance intervals and ensures excellent lubrication of the bearings while offering an excellent protection throughout.

RotEnergyFood 46 cSt synthetic oil

C600000025A	1 x 5-litre can (4.20 kg)
C600000016A	1 x 19-litre can (18.5 kg)
C600000017A	1 x 208-litre drum (175 kg)

A high quality lubricant for rotary compressors, suitable for use in the food industry, where specific quality standards are required.

Our FSN mineral or synthetic based lubricants are specifically designed for use on our screw compressors. They are available in cans or drums in various sizes.

We recommend replacing the oil according to the interval reported in the handbook / maintenance manual of the compressor or once a year if sooner.

We recommend using our original RotarECOFLUID mineral oils, or RotEnergyPlus and RotEnergyFood synthetic oils (OILS ARE NOT INCLUDED IN LONG LIFE KITS).



You can download the Long Life Kit catalogues from the nuaircompressors.com website and see the exploded diagrams and spare parts list online. They are continuously updated for each compressor model.

FNA S.p.A. L. Via Einaudi, 6
10070 Robassomero Torino ITALY
T: +39 011 92 33 000 F: +39 011 92 41 138

BOLOGNA PLANT:
Via Toscana, 21 40069 Zola Predosa Bologna ITALY
T: +39 051 61 68 111 F: +39 051 75 24 08
info@fnacompressors.com
www.fnacompressors.com



AUTHORISED DISTRIBUTOR:



a brand of



Follow us on: [LinkedIn](#)



nuaircompressors.com